








Vacuum System Accessories



Tube Fittings for SLSA-3 Series Suspensions

Tube fittings are purchased separately to connect the spring loaded suspension assembly to the vacuum hose. They are available in barbed, push-in, and compression connections, with straight, elbow, and tee configurations. These fittings accept tubes with standard inside and outside diameters. All fittings are electro-less nickel-plated.

Fitting Type	ANVER Item No.	Description	L in (mm)	H in. (mm)
	A1414B	Hose Barb, 1/4" NPT to 1/4" ID Hose	0.83 (21)	2.52 (64)
	HS14-14F	1/4" NPT Female Coupling		
	PCE14F-14F	Push Connect Elbow 1/4" NPT (Female) to 1/4" OD Tube (Female)	1.18 (30)	1.18 (30)
	PCT14FB-14F	Push Connect Tee 1/4" NPT (Female Bottom) to 1/4" OD Tube (Female)	1.18 (30)	1.18 (30)
	HS18-14F	Reducing Coupling 1/4" NPT (Female) to 1/8" NPT (Female)	0.87 (22)	0.98 (25)
	HS14-38M	Reducing Bushing 3/8" NPT (Male) to 1/4" NPT (Female)	0.87 (22)	0.75 (19)
	2200P-4-4	Elbow, 90° 1/4" NPT (Female)	1.18 (30)	1.18 (30)
	HS14-14M-G	Adapter G 1/4" - male to 1/4" NPT - female	0.75 (19)	0.91 (23)

► This spec sheet was adapted for print from our website. Additional information and photos are available at www.anver.com. 7032401